



SinoCleansky
Super Cylinder Supply

Cryogenic Cylinder

"We SinoCleansky vast array of models offer everything you need to transport store and dispense liquefied gases safely and securely"



Product Features

- Technology: high-vacuum multi-layer insulation
- Application: LOX, LIN, LAR, LCO₂, LNG storage and transportation.
- Standard: DOT-4L, EN1251, GB24159, ASME, and other international standards
- High-performance super insulation
- Minimum product vapor loss
- Convenient storage and transportation
- Customized vaporization coils provide constant gas flow rates

Product Introduction

Manufacturing standards: DOT-4L, EN1251, GB (Chinese standard), etc.

Water capacity: 175 L - 500L

Working pressure: 1.37MPa, 2.02MPa, 2.4MPa, 2.84MPa etc.

Typical types (Vertical)

Standard	Type
EN1251	EN200HP(216L-2.4 MPa)
EN1251	EN160HP(175L-2.4 MPa)
EN1251	EN180HP(197L-2.4 MPa)
DOT-4L	CT160HP(175L-2.02MPa)
DOT-4L	CT180HP(195L-2.02MPa)
DOT-4L	CT200HP(205L-2.02MPa)
DOT-4L	CT240HP(250L-2.02MPa)

Standard	Type
GB24159	DPL452-175-1.37 MPa
GB24159	DPL452-195-1.37 MPa
GB24159	DPL450-210-1.37 MPa
GB24159	DPL450-175-2.02 MPa
GB24159	DPL450-195-2.02 MPa
GB24159	DPL450-210-2.02 MPa
ASME	BC500-208L-2.07MPa(LCO ₂)
ASME	BC750-344L-2.07MPa(LCO ₂)





SinoCleansky
Super Cylinder Supply

Big capacity popular types (Vertical / Horizontal optional)

Standard	Type
GB24159	DPL700-450-1.59 MPa
GB24159	DPW650-499-1.59MPa
GB24159	DPL700-500-1.59MPa
GB24159	DPW650-499-2.5MPa
GB24159	DPW650-500-2.4MPa
GB24159	DPL700-500-2.88MPa
GB24159	DPL700-500-3.5MPa



Customized Model Case

Type number: DPL700-500-1.59MPa

Manufacture standard: GB24159

Water capacity: 500L

Working pressure: 1.59MPa

Filling Medium: LOX / LIN / LAr

Vaporization: $\leq 30\text{Nm}^3/\text{h}$



Detail pictures



Vaporizer



Name card



Valves



Pressure gauge

Shipment

