



SinoCleansky
Gas Container & Solution



High Pressure Seamless Steel Gas Cylinder

“More than 1,500,000pcs supplied since year 2006 ”

We SinoCleansky provide all types of steel gas cylinder. Our products are manufactured according to the GB5099, ISO9809, EN ISO9809 (TPED), DOT-3AA and other international standards. We provide the third-party test reports for our cylinders, such as TUV, Lloyd's Register, DNV, etc.

SinoCleansky cylinders are widely used for Oxygen (O_2), Nitrogen (N_2), Argon (Ar), Carbon Dioxide (CO_2), Helium (He), Nitrous Oxide (N_2O), Hydrogen (H_2) and so on, which covers industrial, fire-fighting, energy, medical, city construction and other sectors.

-  Industrial gas cylinder
-  Medical cylinder
-  Billet-pierced cylinder
-  Fire-fighting gas cylinder

Specifications

Manufacturing standard:

ISO9809, EN ISO9809 (TPED), DOT-3AA, GB5099

Water capacity: 0.5L - 200L

Working pressure: 15MPa, 20MPa, 23MPa, 30MPa

Outer diameter: 108mm - 406mm etc



Detail Pictures





SinoCleansky
Gas Container & Solution

Typical types

Industrial gas cylinder & Medical cylinder

Standard	Type	Outer diameter	Water capacity	Working pressure
GB5099/ISO9809	WMA140-15MPa-10L	140 mm	10 L	15 MPa
GB5099/ISO9809	WMA219-15MPa-40L	219 mm	40 L	15 MPa
GB5099/ISO9809	WMA232-15MPa-47L	232 mm	47 L	15 MPa
EN ISO9809	OD232-20MPa-50L	232 mm	50 L	20 MPa
EN ISO9809	OD229-30MPa-50L	229 mm	50 L	30 MPa
DOT-3AA	20CF (MC10)	133 mm	3.6 L	2015 psi
DOT-3AA	40CF (B40)	178 mm	7.8 L	2015 psi
DOT-3AA	225CF	229 mm	43.3 L	2015 psi

Popular Billet-Pierced cylinder

Standard	Type	Outer diameter	Water capacity	Working pressure
ISO9809	OD229-20MPa-40L	229 mm	40 L	20 MPa
ISO9809	OD229-20MPa-50L	229 mm	50 L	20 MPa
EN ISO9809	OD232-23MPa-47L	232 mm	47 L	23 MPa
ISO9809	OD229-30MPa-50L	229 mm	50 L	30 MPa
EN ISO9809	OD267-20MPa-80L	267mm	80 L	20 MPa
ISO9809	OD267-30MPa-80L	267mm	80 L	30 Mpa

Fire-fighting gas cylinder (CO₂)

Standard	Type	Outer diameter	Water capacity	Working pressure
GB5099	WZA267-15MPa-68L/67.5L	267 mm	67.5 L/68 L	15 MPa
EN ISO9809	OD267-15MPa-68L/67.5L	267 mm	67.5 L/68 L	15 MPa
EN ISO9809	OD267-20MPa-68L	267 mm	68 L	20 MPa
EN ISO9809	OD267-30MPa-68L	267 mm	68 L	30 MPa
EN ISO9809	OD267-20MPa-80L	267 mm	80 L	20 MPa
EN ISO9809	OD267-30MPa-80L	267 mm	80 L	30 MPa
EN ISO9809	OD356-20MPa-140L	356 mm	140 L	20 Mpa
EN ISO9809	OD356-30MPa-140L	356 mm	140 L	30 Mpa

Shipment



Shipment



Plastic net



Carton box



Pallet



Full Container